



HEALTH	2
FLAMMABILITY	4
REACTIVITY	1

MATERIAL SAFETY DATA SHEET

Prepared by Duro Dyne January 7, 2011

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade name: DURO DYNE DYN-O-COAT EDGE COATING
Product Identifier: DCEC- 14 OZ.
Supplier Details: DURO DYNE CORPORATION
81 Spence Street
Bay Shore, NY 11706

Information

Phone No: 800-899-3876
Emergency Phone No: 800-424-9300 (CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN	ACGIH		OSHA		COMPANY	
				TLV TWA	TLV STEL	PEL TWA	PEL CEILING	TLV TWA	SKIN
01	ISOHEXANE	107-83-5	30.0%	500ppm	1000ppm	N.E.	N.E.	N.E.	No
02	PROPANE	74-98-6	25.0%	2500ppm	N.E.	1000ppm	N.E.	N.E.	No
03	ACETONE	67-64-1	15.0%	500ppm	750ppm	1000ppm	N.E.	N.E.	No
04	DIMETHYL ETHER	115-10-6	10.0%	N.E.	N.E.	N.E.	N.E.	1000ppm	No
05	TOLUENE	108-88-3	5.0%	20ppm	N.E.	200ppm	300ppm	N.E.	Yes
06	N-PENTANE	109-66-0	5.0%	600ppm	N.E.	1000ppm	N.E.	N.E.	No

3. HAZARDS IDENTIFICATIONS

Emergency Overview:

Keep from reach of children. Do not puncture, incinerate, or place aerosol product containers in compactors. Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Effects of Overexposure:

Eye Contact: Can cause severe irritation, redness, tearing, blurred vision.

Skin Contact: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation.

Ingestion: No information.

Chronic Hazards: Overexposure to this material (or its components) has apparently been found to cause the following effects in laboratory animals: kidney damage, eye damage, liver damage, lung damage, hearing loss.
Overexposure to this material (or its components) has apparently been found to cause the following effects in humans: liver damage, kidney damage, brain damage.

Primary Route(s) of Entry: Skin contact, skin absorption, inhalation, eye contact.

4. FIRST AID AND EMERGENCY MEASURES

Eye Contact: Flush with large amounts of water, lifting upper and lower lids occasionally, get medical attention.

Skin Contact: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. Get medical attention if irritation persists.

Inhalation: Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.

Ingestion: Do not induce vomiting. Give two glasses of water if conscious, Never give anything by mouth to an unconscious person. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash Point (Pensky-Martens C.C.): -156°F

Lower Explosive Limit: 1.0%

Upper Explosive Limit: 18.0%

Autoignition Temperature: N.D.

Extinguishing Media: CO₂, dry chemical, foam, water fog.

Unusual Fire and Explosion Hazards: Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignition sources at locations distant from the material handling point. For aerosol products-expose to temperatures over 130°F may cause containers to burst releasing highly flammable gas.

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus with a full-face piece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

6. ACCIDENTAL RELEASE MEASURE

Spill Response:

Eliminate sources of ignition and ventilate area. Persons not properly equipped should be excluded from area. Stop spill at source-prevent spreading. Avoid inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into proper container for disposal. Use non-sparking scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.

7. HANDLING AND STORAGE

Handling:

Containers of this material may be hazardous when emptied, since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch on containers. Intentional misuse by deliberately concentrating and inhaling the vapors from this product may be harmful or fatal.

Storage Temperature:

Do not store above 120°F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks, and other sources of ignition. Do not store above 120°F. Do not store in direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:

Provide sufficient mechanical ventilation (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Respiratory Protection:

If work place exposure limits of product or any component is exceeded, use a NIOSH/MSHA approved respirator. Consult your safety equipment supplier for recommendations.

Skin Protection:

Wear impervious gloves if method of use involves skin contact with product. Consult your safety supply vendor for glove recommendations,

Eye Protection:

Wear safety glasses at minimum, more extensive protection may be necessary depending on how the product is to be used.

Other Protective Equipment:

Wear impervious clothing if bodily exposure is anticipated. Consult your safety supply vendor for recommendations.

Hygienic Practices: Wash hands before eating or smoking. Smoke in designated areas only. Remove and launder clothing if contaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Range: -44 –500°F.
Odor: Mint when wet.
Appearance: Black liquid.
Solubility in H₂O: Negligible.
Freeze Point: N.D.
Vapor Pressure: N.D.
Physical State: Liquid
Coefficient of Water/Oil
Distribution: N.D.
Vapor Density: Is heavier than air.
Odor Threshold: N.D.
Evaporation Rate: Is faster than Butyl Acetate.
Specific Gravity: 0.6972
PH @ 0.0%: N.D.
Viscosity: N.D.

(See Section 16 for abbreviation legend)

10. STABILITY AND REACTIVITY

Conditions to Avoid: Heat, sparks, welding arcs, open flame, pilot lights, static electricity or other source of ignition.
Incompatibility: Oxidizing agents, acids, amines, reducing agents strong oxidizers, very strong acid, caustic or oxidizing agents.
Hazardous Decomposition Products: Carbon monoxide and carbon dioxide, various hydrocarbons, aldehydes, carboxylic acids.
Hazardous Polymerization Conditions: Will not occur under normal conditions.
Stability: This product is stable under normal storage conditions.

11. TOXICOLOGICAL INFORMATION

No product or component toxicological information is available.

12. ECOLOGICAL INFORMATION

No information.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose of in accordance with all local, state and federal regulations.

14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name: Aerosols
DOT Technical Name: N/A
DOT Hazard Class: 2.1
Hazard Subclass: None.
DOT UN/NA Number: UN1950
Packing Group: None.
Resp: Guide Page 126
Additional Information: For domestic ground and air shipment this product may be shipped as a Consumer Commodity ORM-D. Outer cartons must have the ORM-D or ORM-D AIR designation. (Original cartons are preprinted with the ORM-D designation for ground shipment).

15. REAGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

CERLA-SARA Hazard Category: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:
IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

SARA Section 313: This product contains the following substances subject to the reporting requirements of Section 313 of the Title III of the Superfund Amendments and Reauthorization Act of 1986 and CFR Part 372:
Chemical Name: Toluene
CAS Number: 108-88-3
WT/WT % is less than: 5.0%

Toxic Substances Control Act: This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:
Chemical Name: No information is available.
CAS Number: No information is available.

INTERNATIONAL REGULATIONS: AS FOLLOWS

Canadian WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for the 16 headings.

Canadian WHMIS Regulations: No information available.

TSCA Inventory: All components of this product are on the US TSCA inventory. On June 30,1993 the OSHA Z-1-A table was revoked and OSHA reverted back to their prior exposure limits. The values on this MSDS reflect to roll back to the prior values. Some states may continue to

enforce the 1993 limits. On June 16, 1995 EPA announced in a final rule that acetone would no longer be considered a VOC for the air attainment standards (It is now an exempt compound). The VOC calculations on this MSDS are based on acetone being an exempt compound. The June 16 rule also removed acetone from the list of SARA 313 reportable chemicals.

16. OTHER INFORMATION

Hazard Rating:	Health: 2 Flammability: 4 Reactivity: 1
Date MSDS Prepared:	April 23,2009
Volatile by Weight:	75.3%
Volatile by Volume:	82.7%
VOC Content:	64.8% by weight 451 grams/liter total product 497 grams/liter less water and exempt 0.58 lbs/can
Legend:	N.A – Not Applicable N.E – Not Established N.D.- Not Determined

THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE. BECAUSE SOME OF THE INFORMATION IS DERIVED FROM INFORMATION PROVIDED TO DURO DYNE CORPORATION FROM ITS SUPPLIERS, DURO DYNE CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE USE OF THIS INFORMATION AND THE CONDITIONS AND USE OF THIS PRODUCT ARE CONTROLLED BY THE USER, IT IS THE USER'S OBLIGATION TO DETERMINE THE CONDITIONS OF SAFE USE OF THE PRODUCT. THE INFORMATION IS SUPPLIED FOR YOUR INFORMATION AND CONSIDERATION AND DURO DYNE CORPORATION ASSUMES NO RESPONSIBILITY FOR USE OR RELIANCE THEREON. IT IS THE RESPONSIBILITY OF THE USER OF DURO DYNE CORPORATION PRODUCTS TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.