

## Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

**Material Name**

Sure-Grip 404

**Synonyms**

Solvent-based mastic

**Chemical Family**

Mastic

**Product Use**

Duct sealant

**Restrictions on Use**

For industrial use only

**Manufacturer Information**

Carlisle HVAC Products

900 Hensley Lane

Wylie, TX 75098

www.carlislehvac.com

**Medical Emergency:**

**CHEMTREC (USA): (800) 424-9300**

MSDS Assistance – 972-442-6545

Technical Assistance – 888-229-2199

Customer Service – 888-229-0199

---

### Section 2 - HAZARDS IDENTIFICATION

---

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Flammable Liquids - Category 2

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Reproductive Toxicity - Category 1A

Specific Target Organ Toxicity - Repeated Exposure - Category 2

**GHS Label Elements**

**Symbol(s)**





## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

**Signal Word**

Danger

**Hazard Statement(s)**

Highly flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May damage fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

**Precautionary Statement(s)**

**Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

**Response**

In case of fire: Use appropriate media to extinguish

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Specific treatment (see label)

**Storage**

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

**Other Hazards**

No additional information available.



## Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Trade Secret	Styrene butadiene polymer	5-10
Trade Secret	Polyphenol antioxidant	0.1-1
1314-13-2	Zinc oxide	1-5
21645-51-2	Aluminum hydroxide	5-10
108-88-3	Toluene	7-13
64742-89-8	Heptane	10-30

### Section 4 - FIRST AID MEASURES

#### Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

Remove/Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs, get medical advice/attention.

#### Eyes

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

#### Ingestion

If swallowed, get medical attention. Do NOT induce vomiting.

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

#### Most Important Symptoms/Effects

##### Acute

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause gastrointestinal irritation.

##### Delayed

May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure: kidney, liver.



## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

### Note to Physicians

Contains organic solvents: heptane, toluene.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### Extinguishing Media

#### Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide. Water may be ineffective. Use water spray to keep containers cool.

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

#### Special Hazards Arising from the Chemical

Can burn and explode easily when exposed to open flames or high heat.

#### Hazardous Combustion Products

oxides of carbon, oxides of nitrogen

#### Special Protective Equipment and Precautions for Firefighters

Highly flammable liquid and vapor. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

#### Fire Fighting Measures

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools. Dike for later disposal.

### Environmental Precautions

Avoid release to the environment.

---

## Section 7 - HANDLING AND STORAGE

---

### Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do



# Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wash contaminated clothing before reuse. **KEEP OUT OF REACH OF CHILDREN.**

**Conditions for Safe Storage, Including any Incompatibilities**

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Keep away from heat and ignition sources. Keep away from incompatible materials. Do not cut, puncture, or weld on or near this container.

**Incompatible Materials**

Strong oxidizing agents, acids, bases

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Component Exposure Limits

<b>Limestone</b>	1317-65-3	
NIOSH:	10 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable dust	
OSHA (US):	15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT	20 mg/m <sup>3</sup> STEL [LMPE-CT]
<b>Zinc oxide</b>	1314-13-2	
ACGIH:	2 mg/m <sup>3</sup> TWA respirable fraction	10 mg/m <sup>3</sup> STEL respirable fraction
NIOSH:	5 mg/m <sup>3</sup> TWA dust and fume	10 mg/m <sup>3</sup> STEL fume
	15 mg/m <sup>3</sup> Ceiling dust	500 mg/m <sup>3</sup> IDLH
OSHA (US):	5 mg/m <sup>3</sup> TWA fume; 15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction	
Mexico:	5 mg/m <sup>3</sup> TWA LMPE-PPT fume; 10 mg/m <sup>3</sup> TWA LMPE-PPT dust	
	10 mg/m <sup>3</sup> STEL [LMPE-CT] fume	
<b>Clay</b>	1332-58-7	
ACGIH:	2 mg/m <sup>3</sup> TWA particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	
NIOSH:	10 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable dust	
OSHA (US):	15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction	

## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT	20 mg/m <sup>3</sup> STEL [LMPE-CT]
<b>Silica gel</b>	112926-00-8	
ACGIH:	10 mg/m <sup>3</sup> TLV-TWA	
NIOSH:	6 mg/m <sup>3</sup> TWA	3000 mg/m <sup>3</sup> IDLH
OSHA (US):	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> )) mg/m <sup>3</sup> TWA)	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT	
<b>Toluene</b>	108-88-3	
ACGIH:	20 ppm TWA	150 ppm STEL
NIOSH:	100 ppm TWA; 375 mg/m <sup>3</sup> TWA	150 ppm STEL; 560 mg/m <sup>3</sup> STEL
	500 ppm IDLH	
Europe:	50 ppm TWA; 192 mg/m <sup>3</sup> TWA	100 ppm STEL; 384 mg/m <sup>3</sup> STEL
	Possibility of significant uptake through the skin	
OSHA (US):	200 ppm TWA	150 ppm STEL
	300 ppm Ceiling	
Mexico:	50 ppm TWA LMPE-PPT; 188 mg/m <sup>3</sup> TWA LMPE-PPT	
	Skin - potential for cutaneous absorption	
<b>Heptane</b>	64742-89-8	
NIOSH:	85 ppm TWA	440 ppm STEL
	500 ppm IDLH	
OSHA (US):	400 ppm TWA	500 ppm STEL

**Biological limit value**

There are no biological limit values for any of this product's components.

**Engineering Controls**

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.



## Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Safety glasses or goggles are recommended when there is a potential for eye contact. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

#### Skin Protection

Wear appropriate work clothing. Wear protective shoes. Recommended material: protective skin cream.

#### Respiratory Protection

In case of inadequate ventilation wear respiratory protection. Appropriate respirator selection should be made by a qualified professional as part of a comprehensive respiratory protection program as described in 29 CFR 1910.134.

#### Glove Recommendations

Wear protective gloves. Recommended material: nitrile.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	gray mastic	<b>Physical State</b>	solid
<b>Odor</b>	mild,hydrocarbon odor	<b>Color</b>	gray
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	-95 °C (-139 °F)	<b>Boiling Point</b>	90 - 111 °C (194-231 °F)
<b>Freezing point</b>	Not available	<b>Evaporation Rate</b>	3
<b>Boiling Point Range</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition</b>	230 °C (475 °F)	<b>Flash Point</b>	-7.2 °C (19 °F)
<b>Lower Explosive Limit</b>	1 %	<b>Decomposition</b>	Not available
<b>Upper Explosive Limit</b>	7 %	<b>Vapor Pressure</b>	45 mmHg
<b>Vapor Density (air=1)</b>	3.4	<b>Specific Gravity (water=1)</b>	Not available
<b>Water Solubility</b>	Negligible	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	450000 cps	<b>Solubility (Other)</b>	Hydrocarbons
<b>Density</b>	1 - 1.2 (relative)	<b>VOC</b>	395 g/L
<b>Volatility by Weight</b>	30 - 40 %		

#### Other Information

No additional information available.



## Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

---

### Section 10 - STABILITY AND REACTIVITY

---

#### Reactivity

No reactivity hazard is expected.

#### Chemical Stability

Stable under normal conditions of use.

#### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

#### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

#### Incompatible Materials

Strong oxidizing agents, acids, bases

#### Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

---

### Section 11 - TOXICOLOGICAL INFORMATION

---

#### Information on Likely Routes of Exposure

##### Inhalation

May cause respiratory irritation.

##### Skin Contact

Causes skin irritation.

##### Eye Contact

Causes serious eye irritation.

##### Ingestion

May cause gastrointestinal irritation.

#### Acute and Chronic Toxicity

##### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Polyphenol antioxidant (Trade Secret)

Oral LD50 Rat >200 mg/kg

Dermal LD50 Rabbit >5010 mg/kg

Inhalation LC50 Rat >165 mg/L 1 h

Zinc oxide (1314-13-2)

Oral LD50 Rat >5000 mg/kg

Aluminum hydroxide (21645-51-2)

Oral LD50 Rat >5000 mg/kg





## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

Toluene (108-88-3)

Oral LD50 Rat 2600 mg/kg

Dermal LD50 Rabbit 12000 mg/kg

Inhalation LC50 Rat 12.5 mg/L 4 h

Heptane (64742-89-8)

Oral LD50 Mouse 5000 mg/kg

Dermal LD50 Rabbit 3000 mg/kg

### Immediate Effects

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause gastrointestinal irritation.

### Delayed Effects

May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure: kidney, liver.

### Irritation/Corrosivity Data

May cause skin irritation. Causes serious eye irritation. May cause respiratory irritation.

### Respiratory Sensitization

No data available.

### Dermal Sensitization

It may cause sensitization in some individuals.

### Component Carcinogenicity

<b>Clay</b>	1332-58-7
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
DFG:	Category 3B (could be carcinogenic for man)
<b>Silica gel</b>	112926-00-8
IARC:	Monograph 68 [1997] (Group 3 (not classifiable))
<b>Toluene</b>	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))

### Germ Cell Mutagenicity

No data available.

### Reproductive Toxicity

May damage fertility or the unborn child.



## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

**Specific Target Organ Toxicity - Single Exposure**

No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

May cause damage to organs through prolonged or repeated exposure: kidney, liver.

**Aspiration hazard**

No data available.

**Medical Conditions Aggravated by Exposure**

No data available.

**Additional Data**

No additional information available.

---

### Section 12 - ECOLOGICAL INFORMATION

---

**Ecotoxicity**

Avoid release to the environment.

**Component Analysis - Aquatic Toxicity**

<b>Polyphenol antioxidant</b>	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >0.2 mg/L [semi-static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata >0.2 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >0.2 mg/L IUCLID
<b>Toluene</b>	108-88-3
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID



## Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

Heptane	64742-89-8
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID

### Persistence and Degradability

No information available for the product.

### Bioaccumulative Potential

No information available for the product.

### Mobility

No information available for the product.

### Other Toxicity

No additional information available.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

### Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

---

## Section 14 - TRANSPORT INFORMATION

---

### US DOT Information:

Shipping Name: Adhesives

Hazard Class: 2

UN/NA #: UN1133

Packing Group: II

Required Label(s): Red caution label required (limited quantity if < 0.3 gal)

### IATA Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

Required Label(s): 3

### TDG Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

Required Label(s):



# Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

## Section 15 - REGULATORY INFORMATION

### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ

### SARA Section 311/312 (40 CFR 370 Subparts B and C)

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Zinc oxide	1314-13-2	Yes	Yes	Yes	Yes	Yes
Clay	1332-58-7	No	Yes	Yes	Yes	Yes
Silica gel	112926-00-8	No	Yes	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes

### The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity , initial date 1/1/91
	female reproductive toxicity , initial date 8/7/09

### Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Zinc oxide	1314-13-2
	1 %

## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

Toluene	108-88-3
	1 %

**Component Analysis - Inventory**

Polyphenol antioxidant (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Zinc oxide (1314-13-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Clay (1332-58-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Aluminum hydroxide (21645-51-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Silica gel (112926-00-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Toluene (108-88-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX



# Safety Data Sheet

Material Name: Sure-Grip 404

Product #: 302014

Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
-----	-----	-----	-----	-----	-----	----	-----	----	-----	-----	-----

Heptane (64742-89-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

## Section 16 - OTHER INFORMATION

### NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Summary of Changes

New SDS: May 20, 2015

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.



## Safety Data Sheet

**Material Name: Sure-Grip 404**

**Product #: 302014**

### **Other Information**

#### **Disclaimer:**

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.